

RF Wireless Transmitter Module: TB-03

Feature:

Model No.: 0021036 (TB-03)

Size: 41mm x 20mm x 10mm

Working Voltage: DC 3~12V

Working Current: 6~12mA

RF Sensitivity: -103dBm

Transmitting Distance: 50m / 150ft (in open field)

Transmitting Power: 10dBm (10mW)

Modulation Method: Amplitude modulation (ASK or OOK)

Encoding Mode: Pins

Working Temperature: -20°C ~ +70°C

Frequency: We can offer 315 MHz or 433.92 MHz, you can choose one

Oscillation resistor / Timing resistor: We can offer 1.2M, 1.5M, 1.8M, 2.2M, 3.3M or 4.7M, you can choose one.

Reliable Control: Use an 8-bit code (Encoding).

Stable performance; using SAW (surface acoustic wave) to stabilize frequency

Wide working voltage range, large transmitting power and long transmission distance

Application:

Used for wireless calling system, burglar alarm, wireless data transmission, auto data collection system and so on.

Applied with our receivers

Notes:

The transmitting frequency, encoding mode and timing resistor should be compatible with the receiver.

It is best to use the antenna of 1/4 wavelength, for antenna has a great impact on receiving effect of the module; normally using 50Ω single core cable. For frequency 315MHz, the length of antenna is about 23cm; for 433MHz, it is about 17cm.

The position of antenna also affects the receiving effect of the module. When installing the antenna should be extended as much as possible and be away from the shield and the place in high pressure and interference.

Introduction of pin:

Pin	Function
D0	data pin
D1	data pin
D2	data pin
D3	data pin
VCC	positive power supply
GND	negative power supply
ANT	antenna

Codes Area:

Total 12 bits, each bit indicates a code number, such as 0, 1 or 2.

Central Code: A0 ~ A7, it is an 8 numbers code, for example, the central code in chart is 02010000.

Zone Code: D0 ~ D3, it is a 4 numbers code, for example, the zone code in chart is 1121.

